

Spare part SIMATIC S7-300, CPU 318-2 DP, 512 KB work memory, (256 KB Code; 256 KB of data 1st interface MPI 12 Mbit/s; 2 interface PROFIBUS-DP/MPI



General information	
HW functional status	03
Firmware version	V3.0
Engineering with	
<ul style="list-style-type: none"> Programming package 	STEP 7 V5.1 SP2
Supply voltage	
Rated value (DC)	
<ul style="list-style-type: none"> 24 V DC 	Yes
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V
external protection for power supply lines (recommendation)	Miniature circuit breaker; 2 A, type B or C
Input current	
Current consumption (in no-load operation), typ.	1.2 A
Inrush current, typ.	8 A
I^2t	0.4 A ² ·s
Power loss	
Power loss, typ.	12 W

Memory	
Work memory	
• integrated	512 kbyte
Load memory	
• expandable FEPRM	Yes
• expandable FEPRM, max.	4 Mbyte
• integrated RAM, max.	64 kbyte
• expandable RAM	Yes
• expandable RAM, max.	2 Mbyte
Backup	
• present	Yes
• with battery	Yes; all blocks
• without battery	Yes; 11 KB
CPU processing times	
for bit operations, typ.	0.1 μ s
for bit operations, max.	0.1 μ s
for word operations, typ.	0.1 μ s
for fixed point arithmetic, typ.	0.1 μ s
for floating point arithmetic, typ.	0.6 μ s
for timer/counter operations, typ.	0.1 μ s
CPU-blocks	
DB	
• Number, max.	2 047; Number band: 1 to 2047
• Size, max.	64 kbyte
FB	
• Number, max.	1 024; Number band: 0 to 1023
• Size, max.	64 kbyte
FC	
• Number, max.	1 024; Number band: 0 to 1023
• Size, max.	64 kbyte
OB	
• Description	see instruction list
• Number, max.	see instruction list
• Size, max.	64 kbyte
• Number of time alarm OBs	2; OB 10, 11
• Number of delay alarm OBs	2; OB 20, 21
• Number of cyclic interrupt OBs	2; OB 32, 35
• Number of process alarm OBs	2; OB 40, 41
• Number of startup OBs	1; OB 100
• Number of asynchronous error OBs	5; OB 80, 81, 85, 86, 87
• Number of synchronous error OBs	2; OB 121, 122

Nesting depth	
• per priority class	16
• additional within an error OB	3

Counters, timers and their retentivity

S7 counter

• Number	512
Retentivity	
— adjustable	Yes
— preset	Z 0 to Z 7

Counting range

— lower limit	0
— upper limit	999

S7 times

• Number	512
Retentivity	
— adjustable	Yes
— preset	No times retentive

Time range

— lower limit	10 ms
— upper limit	9 990 s

IEC timer

• present	Yes
• Type	SFB

Data areas and their retentivity

Flag

• Number, max.	1 024 byte
• Retentivity available	Yes; MB 0 to MB 1023
• Retentivity preset	MB 0 to MB 15
• Number of clock memories	8; 1 memory byte

Local data

• adjustable, max.	8 192 byte
• preset	3 584 byte
• per priority class, max.	8 192 byte

Address area

I/O address area

• Inputs	8 kbyte
• Outputs	8 kbyte

of which distributed

— Inputs	8 kbyte
— Outputs	8 kbyte

Process image	
• Inputs	2 048 byte
• Outputs	2 048 byte
• Inputs, default	256 byte
• Outputs, default	256 byte
Digital channels	
• Inputs	65 536
— of which central	1 024
• Outputs	65 536
— of which central	1 024
Analog channels	
• Inputs	4 096
— of which central	256
• Outputs	4 096
— of which central	128
Hardware configuration	
Number of expansion units, max.	3
Number of DP masters	
• integrated	2
• via CP	4; CP 342-5
Number of operable FMs and CPs (recommended)	
• FM	16
• CP, PtP	8
• CP, LAN	16
Rack	
• Racks, max.	4
• Modules per rack, max.	8
Time of day	
Clock	
• Hardware clock (real-time)	Yes
• retentive and synchronizable	Yes
• Deviation per day, max.	10 s
Operating hours counter	
• Number	8
• Number/Number range	0 to 7
• Range of values	0 to 32767 hours
• retentive	Yes
Clock synchronization	
• supported	Yes
• to MPI, master	Yes
• to MPI, slave	Yes

- in AS, master
- in AS, slave

Yes
Yes

1. Interface

Interface type	Integrated RS 485 interface
Physics	RS 485
Isolated	Yes
Power supply to interface (15 to 30 V DC), max.	200 mA
Functionality	
• MPI	Yes
• PROFIBUS DP master	Yes
• PROFIBUS DP slave	Yes
• Point-to-point connection	No
MPI	
• Number of connections	32
• Number of nodes, max.	32
• Transmission rate, max.	12 Mbit/s
Services	
— PG/OP communication	Yes
— Global data communication	Yes
— S7 basic communication	Yes
— S7 communication	Yes
— S7 communication, as server	Yes
DP master	
• Transmission rate, max.	12 Mbit/s
• Number of DP slaves, max.	125
Services	
— PG/OP communication	Yes
— Global data communication	No
— S7 basic communication	No
— S7 communication, as server	Yes
— Equidistance	Yes
— SYNC/FREEZE	Yes
— Activation/deactivation of DP slaves	Yes
— Direct data exchange (slave-to-slave communication)	Yes; Transmitter and receiver
Address area	
— Inputs, max.	2 kbyte
— Outputs, max.	2 kbyte
User data per DP slave	
— Inputs, max.	244 byte
— Outputs, max.	244 byte

DP slave	
• Number of connections	12
• Transmission rate, max.	12 Mbit/s
Services	
— PG/OP communication	Yes
— Routing	Yes
Transfer memory	
— Inputs	244 byte
— Outputs	244 byte

2. Interface

Interface type	Integrated RS 485 interface
Physics	RS 485
Isolated	Yes
Power supply to interface (15 to 30 V DC), max.	200 mA
Functionality	
• MPI	No
• PROFIBUS DP master	Yes
• PROFIBUS DP slave	Yes
• Point-to-point connection	No
DP master	
• Number of connections, max.	16
• Transmission rate, max.	12 Mbit/s
• Number of DP slaves, max.	125
Services	
— PG/OP communication	Yes
— Routing	Yes
— Global data communication	No
— S7 basic communication	No
— S7 communication	Yes
— S7 communication, as client	No
— S7 communication, as server	Yes
— Equidistance	Yes
— SYNC/FREEZE	Yes
— Activation/deactivation of DP slaves	Yes
Address area	
— Inputs, max.	244 byte
— Outputs, max.	244 byte
User data per DP slave	
— Inputs, max.	244 byte
— Outputs, max.	244 byte
DP slave	

• GSD file	siem807f.gsg
• Transmission rate, max.	12 Mbit/s
Services	
— Routing	Yes
Transfer memory	
— Inputs	244 byte
— Outputs	244 byte
Communication functions	
PG/OP communication	Yes
Global data communication	
• supported	Yes
• Number of GD packets, transmitter, max.	1
• Number of GD packets, receiver, max.	2
• Size of GD packets, max.	54 byte
• Size of GD packet (of which consistent), max.	32 byte
S7 basic communication	
• supported	Yes
• User data per job, max.	76 byte
• User data per job (of which consistent), max.	76 byte
S7 communication	
• supported	Yes
• as server	Yes
• User data per job, max.	160 byte
S5 compatible communication	
• supported	Yes; via CP and loadable FC
Standard communication (FMS)	
• supported	Yes; via CP and loadable FC
Number of connections	
• overall	32
• usable for PG communication	31
— reserved for PG communication	1
• usable for OP communication	31
— reserved for OP communication	1
• usable for S7 basic communication	30
• usable for S7 communication	30
S7 message functions	
Process diagnostic messages	Yes
simultaneously active Alarm-S blocks, max.	100
Test commissioning functions	
Status block	Yes
Single step	Yes

Number of breakpoints	4
Status/control	
• Status/control variable	Yes
• Variables	Inputs, outputs, memory bits, DB, times, counters
• Number of variables, max.	70
Forcing	
• Forcing	Yes
• Forcing, variables	Inputs, outputs, bit memories, peripheral inputs, peripheral outputs
• Number of variables, max.	256
Diagnostic buffer	
• present	Yes
• Number of entries, max.	100
— adjustable	No
Configuration	
Configuration software	
• STEP 7	Yes; V5.0
Programming	
• Command set	see instruction list
• Nesting levels	8
• System functions (SFC)	see instruction list
• System function blocks (SFB)	see instruction list
Programming language	
— LAD	Yes
— FBD	Yes
— STL	Yes
— SCL	Yes
— CFC	Yes
— HiGraph®	Yes
Software libraries	
— Process diagnostics	Yes
— Software controller	Yes
Know-how protection	
• User program protection/password protection	Yes
Cycle time monitoring	
• lower limit	1 ms
• upper limit	6 000 ms
• adjustable	Yes
• preset	150 ms
Dimensions	
Width	160 mm
Height	125 mm

Depth	130 mm
Weights	
Weight, approx.	930 g
last modified:	04/06/2018